



## CRATEX Elastische Polierstäbe

### Charakteristik:

weiche, gummigebundene SiC Polierstäbe

### Anwendung:

manuell, Feilmaschine, auf der Drehbank

Profil mm	Länge mm	Korn	Bestell-Nr.
Ø 6	150	40 grob	<b>239-046-C</b>
		90 mittel	<b>239-046-M</b>
		120 fein	<b>239-046-F</b>
		240 extra fein	<b>239-046-XF</b>
Ø 9,5	150	40 grob	<b>239-066-C</b>
		90 mittel	<b>239-066-M</b>
		120 fein	<b>239-066-F</b>
		240 extra fein	<b>239-066-XF</b>
Ø 12,5	150	40 grob	<b>239-086-C</b>
		90 mittel	<b>239-086-M</b>
		120 fein	<b>239-086-F</b>
		240 extra fein	<b>239-086-XF</b>
6 x 25	150	40 grob	<b>239-6802-C</b>
		90 mittel	<b>239-6802-M</b>
		120 fein	<b>239-6802-F</b>
		240 extra fein	<b>239-6802-XF</b>
6 x 6	150	40 grob	<b>239-6202-C</b>
		90 mittel	<b>239-6202-M</b>
		120 fein	<b>239-6202-F</b>
		240 extra fein	<b>239-6202-XF</b>
18 x 18	150	40 grob	<b>239-6606-C</b>
		90 mittel	<b>239-6606-M</b>
		120 fein	<b>239-6606-F</b>
		240 extra fein	<b>239-6606-XF</b>